

ZUNCHADORA



Para cinta de acero inoxidable

Código	Referencia	Fuerza de tensión	Rango de tensión	Máximo espesor
85105	S-262	2500 LBS	3/8" hasta 3/4"	0,8mm



85105

■ Material: Acero con tratamiento técnico.

PONCHADORAS

HIDRAÚLICAS



Código	Referencia	Capacidad	Calibre		Mordaza
			mm ²	AGW	
30710	YQ-70	6Ton	6, 8, 10, 16, 25, 35, 50, 70	10, 8, 6, 4, 2, 1/0, 2/0	"C" Abierta
30705	YQ-120	8Ton	10, 16, 25, 35, 50, 70, 95, 120	8, 6, 4, 2, 1/0, 2/0, 3/0, 250MCM	Cerrada
30715	YQ-300A	13Ton	10, 16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300	8, 6, 4, 2, 1/0, 2/0, 3/0, 250, 300, 350, 400, 600 MCM	
30700	EP-430	16Ton	50, 70, 95, 120, 150, 185, 240, 300, 400	1/0, 2/0, 3/0, 250, 300, 350, 400, 600, 800MCM	"C" Abierta



30700



30705-30715



30710

■ Terminales Tubulares no Aisladas

■ Estuche Plastico



Código	Referencia	Tipo	Capacidad	Longitud	Aplicación
30750	TL-2008R	Trinquete	8P8C/RJ-4,6PC6/ PJ-12,6P4C/ RJ-11,4P4C,4P2C	185mm	Terminales de red
30763	FS-051	Manual	Multiservicio	220mm	Multipropósito



30750



30763

PELACABLE AUTOMÁTICO



Código	Referencia	Tipo	Calibre	Longitud (mm)
30775	HS-700B	Automático	20-1 O AWG	175
30770	HS-700D			170



30770



30775

■ **Material:** Acero con tratamiento técnico

SACABOCADOS HIDRÁULICO



Código	Referencia	Troqueles	
83505	T15D10-01	10	1/2"-4"
83510	TPA-8	6	1/2"-2"



83505



83510

- **Espesor máximo para acero:** 3,2 mm (calibre 11)
- **Espesor máximo para acero inoxidable:** 2 mm (calibre 14)
- **Referencia T15d10-01:** Troqueles Para 1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 2 1/2", 3", 3 1/2", 4"

- **REFERENCIA TPA-8:** TROQUELES PARA 1/2", 3/4", 1", 1 1/4", 1 1/2", 2"