



3Polos, 32Amp, Conmutadores (1-0-2)

Diagrama de conexión y dimensiones del producto

32 A 3 Faz Kutup Değiştirici Şalter

32 A 3 Phase Changeover Cam Switch

BAĞLANTI ŞEMASI
CONNECTION DIAGRAM

1	X		X		X	
0						
2		X		X		X

YANDAN GÖRÜNÜŞ
SIDE

ÇERÇEVELER
FRAMES

STANDART ÇERÇEVE
STANDARD FRAME

ALT KAPAK
BOTTOM COVER

ALT KAPAK
BOTTOM COVER

KUT IP 6504

MUHAFAZA KUTUSU
PROTECTION ENCLOSURE

YPT 305 032

KOD
CODE

PROPIEDADES TÉCNICAS

Class:	AC-23A
Corriente operativa nominal (Ie):	32
Tensión nominal de aislamiento (Ui):	690V
Tensión operativa nominal (Ue):	32A. 380-440V AC / 50-60Hz
Vida eléctrica:	min. 10.000 ciclo
Posición total:	3
Estándar:	EN 60947-3
Temperatura de funcionamiento:	-20 / +60 °C
Protección de carcasa de plástico:	-



CAM SWITCH

www.opascompany.com

